

ER-6F

SPORTIER performance. NINJA LOOKS.

± 5,599 / ± 5,999 (ABS) *



Model Year 2010

COLOURS



Pearl Stardust
White / Flat Super
Black



Candy Lime
Green / Flat Super
Black



Ebony / Metallic
Phantom Silver

FEATURES



Quick revving and responsive parallel twin



Sports-style full fairing



Instrument panel



Brakes with optional ABS

SPECIFICATIONS

Engine type	Liquid-cooled, 4-stroke Parallel Twin
Displacement	649 cm ³
Bore x stroke	83 x 60 mm
Compression ratio	11.3:1
Valve/Induction system	DOHC, 8 valves
Fuel system	Fuel injection: ø38 mm x 2 (Keihin)
Ignition	Digital
Starting	Electric
Lubrication	Forced lubrication, semi-dry sump
Transmission	6-speed, return
Final Drive	Sealed Chain
Clutch	Wet multi-disc, manual
Frame type	Diamond, high-tensile steel
Rake/Trail	25° / 106 mm
Wheel travel, front	120 mm
Wheel travel, rear	125 mm
Tyre, front	120/70ZR17M/C (58W)
Tyre, rear	160/60ZR17M/C (69W)
Steering angle, left / right	35° / 35°
Suspension, front	41 mm telescopic fork
Suspension, rear	Offset laydown single-shock with adjustable preload
Brakes, front	Dual semi-floating 300 mm petal discs. Dual piston
Brakes, rear	Single 220 mm petal disc. Single-piston
Dimensions (L x W x H)	2,100 x 760 x 1,200 mm
Wheelbase	1,410 mm
Ground Clearance	145 mm
Seat height	790 mm
Fuel capacity	15.5 litres
Curb Mass	204 kg / 208 kg (ABS)
Maximum power	53 kW {72.1 PS} / 8,500 rpm
Maximum torque	66 N·m {6.7 kgf·m} / 7,000 rpm

* Price includes VAT at 17.5%, delivery to dealer and preparation of motorcycle. Government charges are charged in addition