

VERSYS

unique package

± 5,999 / ± 6,399 (ABS) *



Model Year 2010

COLOURS



Pearl Solar Yellow /
Metallic Flat Spark Black



Metallic Spark Black /
Metallic Flat Spark Black


FEATURES



Low-mid range focused
649cc Parallel Twin



Long travel suspension



Sporty 17" wheels



Upright riding position

SPECIFICATIONS

Engine type	Liquid-cooled, 4-stroke Parallel Twin
Displacement	649 cm ³
Bore x stroke	83 x 60 mm
Compression ratio	10.6:1
Valve/Induction system	DOHC, 8 valves
Fuel system	Fuel injection: ø38 mm x 2 (Keihin)
Ignition	Digital
Starting	Electric
Lubrication	Forced lubrication, semi-dry sump
Transmission	6-speed, return
Final Drive	Sealed chain
Clutch	Wet multi-disc, manual
Frame type	Diamond, high-tensile steel
Rake/Trail	25° / 108 mm
Wheel travel, front	150 mm
Wheel travel, rear	145 mm
Tyre, front	120/70ZR17M/C (58W)
Tyre, rear	160/60ZR17M/C (69W)
Steering angle, left / right	35° / 35°
Suspension, front	41 mm inverted telescopic fork with stepless (right-side) adjustable rebound damping and adjustable preload
Suspension, rear	Offset laydown single-shock with 13-way adjustable rebound damping and 7-way adjustable preload
Brakes, front	Dual semi-floating 300 mm petal discs Caliper: Dual piston
Brakes, rear	Single 220 mm petal disc Caliper: Single-piston
Dimensions (L x W x H)	2,125 mm x 840 mm x 1,330 mm
Wheelbase	1,415 mm
Ground Clearance	180 mm
Seat height	845 mm
Fuel capacity	19 litres
Curb Mass	206 kg (KLE650C) 209 kg (KLE650D)
Maximum power	47 kW {64 PS} / 8,000 rpm. 25 kW {34 PS} / 6,500 rpm (25 kW kit)
Maximum torque	61 Nm {6.2 kgf.m} / 6,800 rpm

* Price includes VAT at 17.5%, delivery to dealer and preparation of motorcycle. Government charges are charged in addition